

Filtration Chemical

INDION® 2814

Alkaline Membrane Cleaner

Application

INDION 2814 is a specially formulated cleaner for removing heavy metal fouling, bio-foulants, slime, polysilicic scales and other colloidal/particulate based foulants from reverse osmosis membranes. INDION 2814 is also effective in removing calcium, silt, organics and metal sulfides.

Benefits & Features

- Highly effective concentrated powder
- Effectively restores membrane performance deteriorated due to scaling
- Harsh on foulants but gentle on membranes

Product Specifications

Appearance	:	Off white to white powder
pH of 2% Aq. solution	:	>11.0
Specific gravity	:	NA
Solubility in water	:	50 g/l
Flash point	:	93.3 °C

Direction for Use

INDION 2814 should be fed in CIP tank to prepare solution for offline cleaning. The dosage and frequency of addition depends upon the severity of fouling/scaling, typical dosages are mentioned below:-

Routine offline cleaning: INDION 2814 is normally recommended at a dose level of 2% solution to be circulated for one hour at low velocity followed by 1-2 hours soaking then one hour high velocity circulation and permeate flushing. It is used against calcium, metal oxides, bio-foulants and other foulants.

Typically it is recommended to be used before acidic or biocidal cleaning for better efficacy, however actual cleaning programme may vary and will be suggested by our IE representative after carefully examining your system.

Limitations and Handling

As with all industrial chemicals, care should be taken in its handling and use. Keep the container closed when not in use, the product should not be swallowed and prolonged contact with the skin should be avoided. Wear goggles, face shield and rubber gloves while handling the product. For detailed safety precautions please refer MSDS.

Storage, Packaging & Shelf Life

INDION 2814 is available in 25 kg pails/bags & 50/200 Kg drums. Shelf life of INDION 2814 is two years under normal handling and storage conditions. It is advisable to keep container tightly closed in a cool place.

The information contained herein, is to the best of our knowledge, true and accurate. No warranty, expressed or implied is made except that the products discussed herein complies with the chemical description. Ion Exchange (India) Ltd. shall not be liable for any incidental or consequential damages arising directly or indirectly in connection with the purchase, use, storage or handling of this product.

INDION is the registered trademark of Ion Exchange (India) Ltd.

ION EXCHANGE (INDIA) LTD.

Corporate Office

Ion House, Dr. E. Moses Road,
Mahalaxmi, Mumbai 400 011
Tel: +91 22 3989 0909
Fax: +91 22 2493 8737
E-mail: ieil@ionexchange.co.in

Chemical Division

4th Flr, Riviera Apartment, Dwarkapuri Colony,
Punjagutta, Hyderabad 500 082
Tel: +91 40 3066 3101 / 02 / 03
Fax: +91 40 3066 3104
E-mail: hydcro@ionexchange.co.in

International Division

R-14, T.T.C MIDC, Thane - Belapur Road,
Rabale, Navi Mumbai 400 701
Tel: +91 22 3989 0909 / 3913 2400
Fax: +91 22 2769 7918
E-mail: export.sales@ionexchange.co.in

OFFICES

Regional	Telephone	Fax	E-mail
Chennai	+91 44 3989 0909 / 3910 2900	+91 44 2815 3361	checro@ionexchange.co.in
Delhi	+91 11 3989 0909 / 3054 3200	+91 11 2577 4837	delcro@ionexchange.co.in
Kolkata	+91 33 3989 0909 / 3043 3400	+91 33 2400 4345	calcro@ionexchange.co.in
Vashi	+91 22 3989 0909 / 3913 2300	+91 22 2788 9839	mumcro@ionexchange.co.in
Branch			
Bengaluru	+91 80 2204 2888	+91 80285 32002	bngcro@ionexchange.co.in
Bhubaneswar	+91 674 326 9525 / 257 1491		bbsr@ionexchange.co.in
Chandigarh	+91 172 274 5011	+91 172 274 4594	delcro@ionexchange.co.in
Hyderabad	+91 40 3066 3101 / 02 / 03	+91 40 3066 3104	hydcro@ionexchange.co.in
Lucknow	+91 522 319 9911	+91 11 2577 4837	lko.general@ionexchange.co.in
Vadodara	+91 265 302 7489 / 90	+91 265 2352 932	brdcro@ionexchange.co.in
Visakhapatnam	+91 891 324 6253		sales.vizag@ionexchange.co.in

Factories: Ankleshwar | Hosur | Patancheru | Rabale | Verna

All India Service and Dealer Network

www.ionindia.com